

### ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwaeht.

- Chiave inclusa
- Key included
- Schlüssel inbegriffen


| Cod. MT    | Mandrino<br>Spindle<br>Spindel | I   | RPM  | Coppia Max<br>Max Torque<br>Max Drehmoment | Reversibile lato<br>mandrino/contromandrino<br>Reversible sub/main<br>spindle side<br>Umkehrbare Spindel-seite/<br>Gegenspindel-seite | Lubr.interna<br>Coolant through<br>Innenkuehlung | Lubr.esterna<br>Ext. coolant<br>Aussenkuehlung | A      | A1   | B  | D    | L    | CHIAVI NON INCLUDE<br>Keys not included<br>Schlüssel nicht einbegriffen |                  |
|------------|--------------------------------|-----|------|--|---|--|--|--------|------|----|------|------|---|------------------|
|            |                                |     |      |  |   |  |  |        |      |    |      |      | CHUB36  | CHSTER20         |
| MNZ0350120 | ER20                           | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | 98.16  | -    | 61 | -    | -    | CHUB36  | CHSTER20         |
| MNZ0350125 | ER25                           | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | 99.16  | -    | 61 | -    | -    | CHUB36  | CHSTER25         |
| MNZ0350132 | ER32                           | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | 102.16 | -    | 61 | -    | -    | CHUB36  | CHSTER32         |
| MNZ0350225 | ER25                           | 1:1 | 6000 | 40Nm                                       | X   | P=70bar  | X  | 99.16  | -    | 71 | -    | -    | CHUB36  | CHSTER25         |
| MNZ0350232 | ER32                           | 1:1 | 6000 | 40Nm                                       | X   | P=70bar  | X  | 102.76 | -    | 71 | -    | -    | CHUB36  | CHSTER32         |
| MNZ0351617 | Ø16x17                         | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | -      | 76.5 | 61 | 16   | 17   | CHUB36  | CH_VTCROCE_M08 * |
| MNZ0352219 | Ø22x19                         | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | -      | 78.5 | 61 | 22   | 19   | CHUB36  | CH_VTCROCE_M10 * |
| MNZ0352721 | Ø27x21                         | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | -      | 79.5 | 61 | 27   | 21   | CHUB36  | CH_VTCROCE_M12 * |
| MNZ0351919 | Ø3/4"x3/4"                     | 1:1 | 6000 | 40Nm                                       | X   | -  | X  | -      | 77   | 61 | 3/4" | 3/4" | CHUB36  | CH_VTCROCE_M08 * |

DMG-MORI

NZ1500/2000 - NZX1500/2000 - NT3100/3150/3200 - NL1500/2000/2500 20 STAZ. - NLX1500/2000/2500 20 STAZ. - NT1000/2000 - NTX500 (BMT40) - NTX1000/2000  
NTX1000/2000/2500/3000 2ND GEN. 12ST. - DURATURN 2050MC/2550MC - ALC/ALX1500/2000/2500 (BMT40) - ECOTURN 450 (BMT40) - NZ DUE/TRE/QUATTRO (BMT40)

MODULO MOTORIZZATO ASSIALE ANGOLARE ±180°  
Axial adjustable angle ±180° driven tool  
Axial angetriebenes Werkzeug schwenkbar ±180°

Subject to change without notice.



M.T. srl

Via Casino Albini 480  
Tel. 0541/956034-957884  
Fax 0541/956341  
47842 S. GIOVANNI IN M. (RN)  
e-mail: mtma@tmarchetti.com  
http://www.tmmarchetti.com



MNZ355-1-00