





ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwaeht.

NKM0130216



- Chiave inclusa
- Key included
- Schlüssel inbegriffen

Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 [Nm]	Reversibile lato mandrino/contromandrino Reversible sub/main spindle side Umkehrbare Spindel-seite/ Gegenspindel-seite	Lubrificazione int. Coolant through Innenkuehlung Pmax [bar]	Lubrificazione est. Ext. coolant Aussenkuehlung	A	H	CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen		
NKM0130216	ER16	1:1	6000	30	X	-	X	115.15	82	CHUB17	CHMNER16	
NKM0130520	ERA20	1:1	6000	30	X	70	X	116.15	87	MNL0210007	CHUB22	CHTAER20ZC •
NKM0130225	ER25	1:1	6000	30	X	-	X	115.61	82	MNL0210007	CHSTER25	
NKM0130425	ER25	1:1	6000	30	X	70	X	128.11	87	MNL0210007	CHSTER25	

NAKAMURA-TOME

WT150/250 - WT150II/250II - WTW150 - WTS150 - SUPER NTM3 - SUPER NTJ - SC150/200/250 - SC200II 12/16 ST.
SC300II 16ST. - NTY3 150(V)/250 - TW10M/MY/MM/MMYY-TW20M/MY/MM/MMYY 16ST. - WY 150(V)/250 - AS200MY 15/12 ST.

MODULO MOTORIZZATO ASSIALE 2 USCITE IN Y H=55mm

Axial single side twin head driven tool in Y H=55mm

Axial angetriebenes Werkzeug 2 Ausgaenge in Y H=55mm

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



NKM260-2-10

Subject to change without notice.

03/2025