



- Chiave inclusa
- Key included
- Schlüssel inbegriffen

DIN 5480

| Cod. MT | Mandrino Spindle Spindel | I (n1:n2) | RPM max n2 | Coppia Max Max Torque Max Drehmoment M2 (Nm) | Lubrificazione int. Coolant through Innenkuehlung Pmax (bar) | Lubr.esterna Ext. coolant Aussenkuehlung | Lav. secco Dry-run Trocken Bearb. | ØD | L | A1 | A2 | A3 | CHIAVI NON INCLUDE Keys not included Schlüssel nicht einbegriffen | |
|------------|--------------------------|-----------|------------|--|--|--|-----------------------------------|----|----|--------|------|-------|---|----------------|
| SAU0240140 | ER40 | 1:1 | 6000 | 70 | - | X | X | - | - | 114 | - | - | CHUB41 | CHSTER40 |
| SAU0240132 | ER32 | 1:1 | 6000 | 70 | - | X | X | - | - | 112.96 | - | - | OKU0650004 | CHSTER32 |
| SAU0970232 | ER32 | 1:1 | 6000 | 70 | 100 (diag. 1) | X | X | - | - | 112.96 | - | - | OKU0650004 | CHSTER32 |
| SAU0240125 | ER25 | 1:1 | 6000 | 70 | - | X | X | - | - | 107.46 | - | - | CHUB41 | CHSTER25 |
| SAU0970225 | ER25 | 1:1 | 6000 | 70 | 100 (diag. 1) | X | X | - | - | 109.96 | - | - | OKU0650004 | CHSTER25 |
| SAU0240320 | WELDON20 | 1:1 | 6000 | 70 | - | X | X | - | - | - | - | 106.3 | - | - |
| SAU0241320 | WELDON20 | 1:1 | 6000 | 70 | 30 | X | - | - | - | - | - | 106.3 | - | - |
| SAU0240525 | WELDON25 | 1:1 | 6000 | 70 | - | X | X | - | - | - | - | 106.3 | - | - |
| SAU0241525 | WELDON25 | 1:1 | 6000 | 70 | 30 | X | - | - | - | - | - | 106.3 | - | - |
| SAU0240416 | Ø16x17 | 1:1 | 6000 | 70 | - | X | X | 16 | 17 | - | 88.3 | - | OKU0650004 | CH_VTCROCE_M08 |
| SAU0240422 | Ø22x19 | 1:1 | 6000 | 70 | - | X | X | 22 | 19 | - | 96.8 | - | CHUB41 | CH_VTCROCE_M10 |

SAUTER
VDI 40
MODULO MOTORIZZATO ASSIALE VDI40 DIN 5480
Axial driven tool VDI40 DIN 5480
Axial angetriebenes Werkzeug VDI40 DIN 5480
Subject to change without notice.

M.T. srl
Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



SAU017-3-00