


ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwaeht.

- Chiave inclusa
- Key included
- Schluesel inbegriffen

Cod. MT	Cod. TAKISAWA	Mandrino Spindel Spindel	I	RPM	Coppia Max Max Torque Max Drehmoment	Lubr.interna Coolant through Innenkuehlung	Lubr.esterna Ext. coolant Aussenkuehlung	A	A1	B	D	L	CHIAVI NON INCLUDE Keys not included Schluesel nicht einbegriffen		
TKW 0140125	-	ER25	1:1	6000	65Nm	-	X	91.16	-	54.5	-	-	-	CHSTER25	OKU0650004 •
TKW 0140132	GM81998-642R	ER32	1:1	6000	65Nm	-	X	93.66	-	54.5	-	-	-	CHSTER32	OKU0650004 •
TKW 0140140	-	ER40	1:1	6000	65Nm	-	X	98.16	-	54.5	-	-	-	CHSTER40	OKU0650004 •
TKW 0140325	-	ERA25	1:1	6000	65Nm	-	X	65	-	54.5	-	-	CHUB27	CHTAER25ZC •	OKU0650004 •
TKW 0140225	-	ER25	1:1	6000	65Nm	P=70bar	X	91.16	-	67	-	-	-	CHSTER25	OKU0650004 •
TKW 0140232	-	ER32	1:1	6000	65Nm	P=70bar	X	93.66	-	67	-	-	-	CHSTER32	OKU0650004 •
TKW 0140240	-	ER40	1:1	6000	65Nm	P=70bar	X	98.16	-	67	-	-	-	CHSTER40	OKU0650004 •
TKW 0140425	-	ERA25	1:1	6000	65Nm	P=70bar	X	65	-	67	-	-	CHUB27	CHTAER25ZC •	OKU0650004 •
TKW 0140516	-	Ø16x17	1:1	6000	65Nm	-	X	-	67.5	54.5	16	17	-	CH_VTCROCE_M08	OKU0650004 •
TKW 0140522	-	Ø22x19	1:1	6000	65Nm	-	X	-	67.5	54.5	22	19	-	CH_VTCROCE_M10	OKU0650004 •
TKW 0140527	-	Ø27x21	1:1	6000	65Nm	-	X	-	70	54.5	27	21	-	CH_VTCROCE_M12	OKU0650004 •

TAKISAWA
 MOD: TMM200/250 - TNR200
 MODULO MOTORIZZATO ASSIALE VDI40
 Axial driven tool VDI40
 Axial angetriebenes Werkzeug VDI40



M.T. srl
 Via Casino Albini 480
 Tel. 0541/956034-957884
 Fax 0541/956341
 47842 S. GIOVANNI IN M. (RN)
 e-mail: mtma@tmarchetti.com
 http://www.tmmarchetti.com



TKW 150-3-15

Subject to change without notice.